



# Clairoy

MAINTENANCE CHEMICALS

## SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

### A10 INDUSTRIAL GRADE PAINT STRIPPER

Revision 3

Revision date 2011-11-09

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name A10 INDUSTRIAL GRADE PAINT STRIPPER

##### 1.3. Details of the supplier of the safety data sheet

Company Clairoy Maintenance Chemicals  
Address 29 Dyson Close,  
Rugby,  
Warwickshire  
CV21 4LG  
Web www.clairoy.co.uk  
Telephone 01788 561722  
Fax 01788 537550  
Email sales@clairoy.co.uk

##### 1.4. Emergency telephone number

Emergency telephone number 01788 561722  
Company CLAIROY MAINTENANCE CHEMICALS  
NORMAL OFFICE HOURS

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC Xn; R20/21/22-40-68/20/21/22  
Symbols: Xn: Harmful.  
Main hazards Harmful by inhalation, in contact with skin and if swallowed. Limited evidence of a carcinogenic effect. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methylene chloride (Dichloromethane)	602-004-00-3	75-09-2	200-838-9		70 - 80%	Carc. Cat. 3; R40
EP 11160 (METHANOL) (Methanol)	603-001-00-X	67-56-1	200-659-6		1 - 10%	F; R11 T; R23/24/25-39/23/24/25
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7		1 - 10%	R10 Xn; R20/21 Xi; R38
METHOCYL					1 - 10%	
PARAFFIN WAX (Paraffin wax, fume)		8002-74-2			1 - 10%	

#### SECTION 4: First aid measures

# A10 INDUSTRIAL GRADE PAINT STRIPPER

Revision 3  
Revision date 2011-11-09

## 4.1. Description of first aid measures

Inhalation	Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Causes burns. Causes severe inflammation and may damage the cornea. Seek medical attention.
Skin contact	Causes burns. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. If swallowed, seek medical advice immediately and show this container or label.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ).
--	--

### 5.2. Special hazards arising from the substance or mixture

	Corrosive. Burning produces irritating, toxic and obnoxious fumes.
--	--

### 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	---

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

### 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Exposure Limit Values

EP 11160 (METHANOL) (Methanol)	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m <sup>3</sup> : 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m <sup>3</sup> : 333
Methylene chloride (Dichloromethane)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m <sup>3</sup> : 350
	WEL 15 min limit ppm: 300	WEL 15 min limit mg/m <sup>3</sup> : 1060
PARAFFIN WAX (Paraffin wax, fume)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m <sup>3</sup> : 2
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m <sup>3</sup> : 6
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m <sup>3</sup> : 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m <sup>3</sup> : 441

### 8.2. Exposure controls

## A10 INDUSTRIAL GRADE PAINT STRIPPER

Revision 3

Revision date 2011-11-09

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus must be used in handling.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State	Viscous liquid.
Colour	Off white
Odour	Characteristic

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity	Harmful by inhalation, in contact with skin and if swallowed. May cause dizziness and headache. Toxic by inhalation. Toxic if swallowed.
Skin corrosion/irritation	Causes burns. May cause degreasing of the skin. May cause severe irritation to skin, eyes and mucous membranes. Risk of serious damage to eyes.

## SECTION 12: Ecological information

## 12.1. Toxicity

	May cause long-term adverse effects in the aquatic environment.
--	---

## 12.2. Persistence and degradability

	Evaporates readily.
--	---------------------

## SECTION 13: Disposal considerations

## General information

	Dispose of in compliance with all local and national regulations.
--	---

## SECTION 14: Transport information

## Hazard pictograms



## 14.1. UN number

	UN2810
--	--------

## 14.2. UN proper shipping name

	TOXIC LIQUID, ORGANIC, N.O.S. (CONTAINS METHANOL)
--	---

## 14.3. Transport hazard class(es)

ADR/RID	6.1
Subsidiary risk	-

## A10 INDUSTRIAL GRADE PAINT STRIPPER

Revision 3

Revision date 2011-11-09

## 14.3. Transport hazard class(es)

IMDG	6.1
Subsidiary risk	-
IATA	6.1
Subsidiary risk	-

## 14.4. Packing group

Packing group	II
---------------	----

## 14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

## ADR/RID

Hazard ID	60
Tunnel Category	(D/E)

## IMDG

EmS Code	F-A S-A
----------	---------

## IATA

Packing Instruction (Cargo)	662
Maximum quantity	60 L
Packing Instruction (Passenger)	654
Maximum quantity	5 L

## SECTION 15: Regulatory information

## Labelling

Symbols	<p>The product is classified in accordance with 67/548/EEC.</p> <p>Xn: Harmful.</p> 
Risk phrases	<p>R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.</p> <p>R40 - Limited evidence of a carcinogenic effect.</p> <p>R68/20/21/22 - Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.</p>
Safety phrases	<p>S23 - Do not breathe gas/fumes/vapour/spray.</p> <p>S27 - Take off immediately all contaminated clothing.</p> <p>S36/37 - Wear suitable protective clothing and gloves.</p> <p>S38 - In case of insufficient ventilation, wear suitable respiratory equipment.</p> <p>S61 - Avoid release to the environment. Refer to special instructions/safety data sheets.</p>

## SECTION 16: Other information

## Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <p>9 - 9.1. Information on basic physical and chemical properties (State).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Colour).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Odour).</p> <p>14 - ADR/RID.</p>
Text of risk phrases in Section 3	<p>R10 - Flammable</p> <p>R11 - Highly flammable.</p> <p>R20/21 - Harmful by inhalation and in contact with skin.</p> <p>R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed.</p>

# A10 INDUSTRIAL GRADE PAINT STRIPPER

Revision 3

Revision date 2011-11-09

---

**Other information**

	R38 - Irritating to skin. R39/23/24/25 - Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R40 - Limited evidence of a carcinogenic effect.
--	---

---

**Further information**

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--